

Safer Micromobility

George Yannis

NTUA Professor

Together with:
Virginia Petraki



Department of Transportation Planning and Engineering
National Technical University of Athens



Philippe Crist


Improving the safety of e-scooter users

Road Safety Performance Index debate - PIN Talk

13 May 2025



Outline



Key Messages

1

Micromobility is becoming safer

But, an increase in severe injuries from e-scooter crashes is cause for concern. Overall, shared e-scooter crash risk is decreasing as their usage is increasing faster than injuries.

2

Safe infrastructure and vehicle design matter

A focus on rider behavior and safety equipment must be complemented by better infrastructure and improved vehicle design – especially for e-scooters.

3


Reinforcing existing policies improves safety

Road safety measures also make micromobility safer – managing speed, providing training to road users and enforcing rules against impaired driving and riding.




What is Micromobility?

- This Report adopts the ITF's **generic approach** to classifying micromobility from a safety perspective – an approach which is descriptive rather than normative.
- This Report focuses on **e-scooters and e-bikes weighing less than ~35 kg**, including models that can travel up to 45 km/h or beyond.



Type A: powered or unpowered vehicles weighing less than 35 kg and with a maximum powered design speed of 25 km/h.



Type B: powered or unpowered vehicles weighing between 35 kg and 350 kg and with a maximum powered design speed of 25 km/h.



Type C: powered vehicles weighing less than 35 kg and with a design speed between 25 km/h and 45 km/h.




Type D: powered vehicles weighing between 35 kg and 350 kg and with a design speed between 25 km/h and 45 km/h.

Micromobility Safety

How to assess micromobility safety?

- Micromobility safety must be addressed in the **broader context of health** since poor safety results in degraded health outcomes.
- **Crash risk** addresses the probability of harm faced by micromobility users.
- **Crashes and injuries** are relevant harms.
 - Investigation of their **occurrence and nature**.
 - Investigation of the factors contributing to the number and severity of crashes – notably **vehicles, riders and infrastructure**.



Methodological Approach

- This report focuses on the safety impact of Micromobility devices and specifically on **e-scooters and e-bikes**
- Both shared and owned e-scooters and e-bikes are considered and throughout the analysis, there is an **effort to differentiate between them**
- An **extensive review** of the scientific and “grey” literature was conducted.
 - Findings at the **international level** were summarized and synthesized
 - **145 relevant studies** were identified and considered appropriate for this review
- A **questionnaire** was crafted and completed by a select group of 5 Micromobility Operators, arranged in alphabetical order:

Bolt


dott

 **Lime**

TIER

voi.

- to gather comprehensive insights into the **safety aspects** encompassing both the physical features and the digital facets of MM vehicles
- to identify **challenges and lessons-learned**






















Safety and Health

- Policy must balance the **positive health contributions** of active modes vs the adverse health outcomes of all micromobility when assessing safety, physical accessibility and other policies.
- Active travel's positive contribution to good health is **far greater** than the negative health impacts of crashes and rider exposure to air pollution.
- From a health perspective, **active and passive forms** of micromobility are not on the same footing.
- While cycling involves physical activity, e-scooters require less effort, but both are linked to **active lifestyles**.
- A **key factor** to consider when looking at micromobility-linked health outcomes is how non-active micromobility replaces walking and cycling vs highly sedentary car travel.



Micromobility Crash Risk

- Crash risk recognizes **that safety is not solely determined by the number of incidents** but is also influenced by how much individuals are exposed to potential risks.
- In 2024, shared e-scooter casualties requiring medical treatment per Mio trips fell **by 25.7% across EU** compared to 2021.
- **Micromobility casualty risk continues to decrease** – 29.8% lower in 2024 compared to 2021 (per Mio km).
- **Lack of data** on micromobility trips and crashes makes it hard to assess micromobility crash risk.
 - Official crash statistics suffer from **underreporting**, showing only part of the crash risk.
 - **Reliable exposure data** – especially for privately owned micromobility trips – is rarely available.

| Shared e-scooter casualties requiring medical treatment per Mio trips | | | | |
|---|---|------|------|--------|
| Market | | 2021 | 2022 | YoY |
| Austria |  | 4.1 | 1.5 | -63.6% |
| Belgium |  | 7.1 | 7 | -1.8% |
| Bulgaria |  | NA | NA | NA |
| Cyprus |  | NA | NA | NA |
| Czech Rep |  | 9.2 | 15.6 | 69.3% |
| Denmark |  | 8.6 | 14.8 | 72.3% |
| Finland |  | 5 | 2.9 | -41.6% |
| France |  | 9 | 12.1 | 34.8% |
| Germany |  | 4.3 | 4 | -7.7% |
| Greece |  | NA | NA | NA |
| Italy |  | 12.1 | 4.4 | -63.3% |
| Norway |  | 3.2 | 2.7 | -17.5% |
| Poland |  | 4.9 | 4.5 | -8.0% |
| Portugal |  | 22.3 | 25 | 12.0% |
| Slovenia |  | NA | NA | NA |
| Spain |  | 22.4 | 14.8 | -34.1% |
| Sweden |  | 5.2 | 5.3 | 0.5% |
| Switzerland |  | 2.2 | 4.4 | 100.3% |
| UK |  | 31.9 | 20.6 | -35.5% |
| Cumulative | | | | -25.7% |

Source: MMfE



Micromobility Crashes

- Most reported micromobility crashes result in only **minor injuries**.
- **Severe injuries** comprise a small portion of total reported injuries, and a relatively small percentage of reported micromobility crashes lead to fatal injuries.
- **Fatality rates** are very low for all injury-inducing crashes (<1%), with no clear difference between e-scooters, e-bikes and conventional bikes.

| Injuries | Vehicle Type | % |
|----------------------------|---------------------------------|-----------|
| Severity | No injury (% of riders) | es 6-9% |
| | Minor injury (% of casualties) | es 56-70% |
| | | eb 65-70% |
| | Severe injury (% of casualties) | es 8-13% |
| | | eb 5-17% |
| | | es <1% |
| Fatality (% of casualties) | | eb <1.3% |
| | cb | <0.2% |

es = electric scooter, eb = electric bike, cb = conventional bike

Casualties: injuries and fatalities.

All sources are detailed in the accompanying technical report.



Micromobility Injury Patterns



- E-scooter injuries are characterised by injuries concentrating in the **head and face**, particularly the lower third (chin and jaw).
- **Upper and lower extremities** injuries are also common among e-scooter crashes.
- E-scooterists presented with a greater share of head, face, and neck injuries **than cyclists**.

| Injuries | | Vehicle Type | % |
|--|-----------------|--------------|------------------------------|
| Injured Body Region (% of casualties) | Upper extremity | es | 25-55% |
| | Lower extremity | es | 23-45% |
| | Head/ Face | es | Head: 18-41% Face: 30-60% |
| | | cb | Head: 20-24% Face: 20% |
| | | eb | Head: 35% |

es = electric scooter, eb = electric bike, cb = conventional bike

Casualties: injuries and fatalities.

All sources are detailed in the accompanying technical report.



Micromobility Crash Types



- Most e-scooter-related crashes involve the rider and no other road user accounting for up to 93% of all reported e-scooter-related casualties.
- E-scooter-related casualties resulting from falls constitute a substantial proportion of overall e-scooter-related casualties (64-85%).
- This range compares with the respective percentage of cyclist single road user collision casualties due to falls (75%).
- Injuries resulting from e-scooter-motor vehicle collisions account for 8-19% of all e-scooter-related casualties, a slightly higher proportion than for bicycle injuries.
- The co-existence of pedestrians and e-scooter riders results in pedestrian injuries (1 to 10% of all e-scooter-related casualties).

| Collisions | | Vehicle type | % |
|---------------------------------------|---|--------------|--------------------------|
| Involved road users (% of casualties) | Single road user | es | 93% |
| | Multiple road users | es | 7% |
| Falls | % of total crashes | es | 79-90% |
| | % of total casualties | es | 64-85% |
| With objects | % of total casualties | cb | 75% |
| | | es | 1-39% |
| With motor vehicles | % of total casualties | es | 8-19% |
| | | cb | 10% |
| | % of total fatalities | es | >86% |
| | | cb | (24% hit-and-run) 93-96% |
| With pedestrians | Involved pedestrians (% of total crashes) | es | 4-17% |
| | Injured pedestrians (% of total casualties) | es | 1-10% |
| | tripped over (of non-rider casualties) | es | 30% |
| | Struck (of non-rider casualties) | es | 59% |
| | | | |

es=electric scooter, eb=electric bike, cb=conventional bike

Casualties: persons injured and fatalities.

All sources are detailed in the accompanying technical report.



Micromobility Crash Factors: Infrastructure

- Safe and convenient **cycling infrastructure** can attract road users to micromobility.
- **Poorly maintained surfaces**, with potholes and other irregularities, contribute to 30-40% of e-scooter crashes.
- **Physically separated and continuous** micromobility infrastructure, existing both on segments and intersections, can enhance safety further.
- **Narrow lane widths** can elevate micromobility crash risk due to proximity to stationary and moving motor vehicles.
- Cycling infrastructure and parking infrastructure are important for **pedestrian safety and comfort**.
- **Speed management – especially of cars** – helps reduce both crashes and their severity.

| Risk factor | Vehicle type | % |
|--|--------------|--|
| Poor road infrastructure (% of tot. crashes) | es | 30-40% |
| Paved vs unpaved road | es | 2.66 greater crash risk |
| Road environment | es | Traffic lane: 23-55% (all) |
| | es | Sidewalk: 17-58% (all) |
| | es | Bike lane: 0.04-25% (all) |
| | es | Intersection: 65% (% of total fatalities) |
| | cb | Intersection: 67% (% of total fatalities) |
| | es | Non-junction: 17% (% of total fatalities) |
| | cb | Non-junction: 17-27% (% of total fatalities) |

es = electric scooter, eb = electric bike, cb = conventional bike

All sources are detailed in the accompanying technical report.



Recommendations: Infrastructure

For Authorities

➤ Proactively maintain micromobility infrastructure

To minimise the risk of micromobility-related crashes caused by potholes, debris etc., authorities should undertake regular maintenance of infrastructure, especially in high micromobility traffic areas.

➤ Establish a dedicated and well-connected micromobility network

Authorities should develop a comprehensive urban plan that incorporates mixed and protected “light traffic lanes” for all micromobility modes, ensuring connectivity with existing transportation networks.

➤ Establish micromobility parking policy and designate parking areas where needed

Authorities should formulate consistent micromobility parking guidelines that enhance its use. This includes establishing clearly marked and well-delineated parking zones for e-scooters and bicycles at the curb or on pedestrian or shared zones, mainly in core urban areas.

For Micromobility Operators

➤ Establish collaborative partnerships with authorities for infrastructure condition reporting

Micromobility operators, armed with valuable data collected through in-vehicle sensors on potholes, falls, and near crashes, should play an active role in the proactive maintenance of urban infrastructure.

➤ Onboard parking zones in shared micromobility apps and deploy smart docking in high-traffic areas

Shared micromobility apps should onboard designated parking areas and restrictions. Deploying smart docking and charging stations in high pedestrian or vehicular traffic zones can reduce obstruction on sidewalks.



Micromobility Crash Factors: Riders

Behaviour, experience and other rider-related factors **strongly correlate** with micromobility safety.

- **RUI:** Injured e-scooterists show **higher alcohol use** compared to conventional bike riders.
- **Helmet use:** In contrast with bicycle riders, injured e-scooter riders display **low levels of helmet-wearing** – even when required by law.
- **Double riding:** Tandem riding contributes to **up to 17%** of all e-scooter related casualties.
- **Visibility:** E-scooter crashes resulting in injuries **predominantly happen** under conditions of low visibility.
- **User experience:** Inexperienced **e-scooter riders** are linked to high crash risk, whether due to a limited number of rides or unfamiliarity with the local context
- **Speeding:** Speeding has been found as a **risk factor for e-scooter injuries** (~30%)

| Risk factor | Vehicle type | Effect |
|--|--------------|---|
| Nighttime (% of fatal crashes) | es | 82% |
| | eb | 48% |
| | cb | 57% |
| | es | 43% |
| Nighttime & Reduced lighting (% of casualties) | es | 30-44% |
| | cb | 14-28% |
| | eb | 18% |
| Nighttime crash risk | es | 4.8 crashes per 100 000 trips vs 2.2 for daytime crashes |
| | | |
| Helmet use (% of casualties) | es | 0-3% |
| | cb | 16-64% |
| | eb | 53% |
| Alcohol | es | Fatalities: 41% |
| | es | Casualties: 7-53% |
| | cb | Casualties: 6-13% |
| Double riding (% of casualties) | es | 14-17%: >one rider/ vehicle |
| | | |
| Experience | es | 24-37% of injuries occurred during the 1 st ride |
| | | |
| | es | 78% of crashes involved riders with low riding rates |

es = electric scooter, eb = electric bike, cb = conventional bike

Casualties: persons injured and fatalities

All sources are detailed in the accompanying technical report.



Recommendations: Riders

For Authorities

- **Implement a 30km/h (or lower) speed limit in areas with high micromobility use**

Authorities should default to 30 km/h (or 20 km/h) speed limits for car and truck traffic in areas with high micromobility traffic.

- **Establish low-speed limits for micromobility vehicles in pedestrian or shared zones**

In areas where micromobility riders legally can or must share pedestrian spaces, authorities should default to establishing a safe (~6-10 km/h) speed limit for micromobility modes to enhance pedestrian safety.

- **Promote the use of appropriate helmets**

Authorities should encourage helmet use for private and shared micromobility in a way that does not discourage using active micromobility, which would diminish overall health benefits.

- **Take enforcement action against risky micromobility riding**

Authorities should impose penalties for illegal micromobility riding, including:

- speeding for micromobility vehicles in speed-restricted zones,
- riding under the influence of drugs and alcohol,
- riding under the age limit,
- riding with two or more people,
- riding on sidewalks when it is forbidden,
- riding outside designated infrastructure where its use is obligatory,
- illegal parking.

- **Introduce rider education in secondary schools**

Micromobility training should be integrated into the curriculum of secondary schools.



Recommendations: Riders

For Micromobility Operators

➤ Provide safety feedback via telematics data

Operators can use telematics data on speeding, acceleration/deceleration or distracted riding to provide riders with post-trip feedback. Real-time safety alerts to riders could also be considered where these do not contribute to rider distraction.

➤ Provide economic incentives for safe riding

Shared micromobility operators may encourage helmet use with economic incentives such as providing free helmets or discounts to encourage safety-conscious ridership.

➤ Implement mandatory initial rider training

To enhance rider safety, shared micromobility operators can require new riders to pass through safe riding screens for the first few rides they make to help ensure that riders are familiar with local rules and guidelines before embarking on their e-scooter trips.

➤ Verify age to start riding

Operators should implement age verification procedures to ensure riders meet the minimum age requirements defined in each city, ensuring compliance with local regulations and safety standards.



Micromobility Crash Factors:

Vehicles (1/2)

- The **rapid uptake of micromobility** vehicles, specifically e-scooters, brings a range of safety concerns linked to vehicle design.
- E-scooters, e-bikes and conventional bicycles **differ greatly** in their design and stability.
- A key distinction between e-scooters and bicycles lies in the **rider's position**.
- The **standing posture** on e-scooters has been identified as risky, particularly during braking to manoeuvre around or away from obstacles.
- The following **design features of micromobility modes** have been found to positively affect MM safety: max design speed limit of powered micromobility vehicles, larger wheels and tires, and foot platform area for e-scooters brakes, back and front lights, bells.





Micromobility Crash Factors:

Vehicles (2/2)

Various e-scooter and bicycle characteristics and safety

E-scooters

Bicycles



Recommendations: Vehicles & Management

For Authorities

➤ Set universal technical requirements for e-scooter design

Establishing and joining technical standards for e-scooters is essential.

E-scooter standards should account for the following:

- maximum speed (e.g. <20/25 km/h. Vehicles operating at higher speeds would be regulated differently and more stringently)
- maximum power (e.g. <250-500 W. Vehicles with higher power should be regulated differently and more stringently)
- minimum wheel size (the larger, the better)
- foot platform area (e.g. at least 150 cm²)
- dual, separate and hand-initiated braking systems
- independent front and rear lights
- indicator lights (due to the difficulties of using handsignals)
- reflective markings
- phone attachment feature.

➤ Adopt riding support systems in micromobility vehicles

Authorities should foster the adoption of riding support systems in micromobility vehicles including automatic emergency braking assistance, audible warning devices providing alerts when speeding, detection technology capable of assessing factors like unsteady movement, occupancy detection sensors and alerts when inappropriately parking.

Safe management

➤ Establish and collect data on distinct micromobility categories in safety statistics

Creating distinct categories for each micromobility mode (i.e., conventional bikes, e-bikes, e-scooters, speed e-scooters/e-bikes, monowheels/e-unicycles) in road traffic casualty records, including police records and medical records, improves safety assessment. Additionally, collecting exposure data for each category is essential to calculate casualty risk accurately.



Recommendations: Vehicles & Management

For Micromobility Operators

➤ Ensure systematic maintenance of micromobility fleets

Operators should maintain their fleets in good repair and follow state-of-the-art maintenance protocols, emphasizing regular checks and upkeep of essential components, including brakes, lights and batteries.

➤ Enable context-dependent maximum speed control using geofencing

Shared micromobility operators can employ geofencing technology to smoothly and dynamically lower maximum speeds to designated speed limits in high-risk zones, such as pedestrian areas or during risky hours like nighttime, prioritising safety for all road users.

➤ Restrict e-scooter access if tandem riding and/or alcohol use is detected

Shared micromobility operators should be encouraged to incorporate in-vehicle sensors to detect tandem riding and introduce in-app tests to identify users under the influence of alcohol and drugs. If violations are detected, e-scooter access can be disabled, ensuring responsible and sober usage.

➤ Implement riding support systems in shared e-scooters

Operators should be encouraged to implement safe riding support systems in e-scooters, including automatic emergency braking assistance and detection technology capable of assessing factors like unsteady movement, tandem riding and inappropriate parking.

Safe management

➤ Enable in-vehicle or in-app crash detection technology

Shared micromobility operators can enhance the safety and user experience of their services and address the low micromobility crash data availability by integrating crash detection technology into their vehicles or mobile applications.



Summary of key Micromobility Risk Factors

A **holistic approach** that combines improved infrastructure, safe riding behaviour, vehicle design standards, and safety and exposure data collection is essential to improve micromobility safety.



| Risk Factors | | Safe Riders | Safe Infrastructure | Safe Vehicles |
|--|--|-------------|---------------------|---------------|
| Safe Riders | | | | |
| Speeding | | ● | ● | ● |
| Helmet use | | ● | ● | ● |
| Under the influence | | ● | ● | ● |
| Visibility | | ● | ● | ● |
| Double riding | | ● | ● | ● |
| User experience/ Riders age | | ● | ● | ● |
| Mobile phone use | | ● | ● | ● |
| Rider's stability | | ● | ● | ● |
| Safe Infrastructure | | | | |
| Poor road infrastructure | | ● | ● | ● |
| Riding location | | ● | ● | ● |
| Parking | | ● | ● | ● |
| Safe Vehicle | | | | |
| Wheel size | | ● | ● | ● |
| Maximum design speed | | ● | ● | ● |
| Braking system | | ● | ● | ● |
| Lights and auditory | | ● | ● | ● |
| E-scooter foot platform | | ● | ● | ● |
| Safe Management | | | | |
| Micromobility safety data availability | | ● | ● | ● |
| Post - care | | ● | ● | ● |

Summary of Micromobility Safety Recommendations

Safe Infrastructure

Proactively maintain micromobility infrastructure (Authorities)

Establish a dedicated and well-connected micromobility network (Authorities)

Establish micromobility parking policy and designate parking areas where needed (Authorities)

Establish collaborative partnerships with authorities for infrastructure condition reporting (Operators)

Onboard parking zones in shared micromobility apps and deploy smart docking in high-traffic areas (Operators)



Safe Riders

Implement a 30km/h (or lower) speed limit in areas with high micromobility use (Authorities)

Establish low-speed limits for micromobility vehicles in pedestrian or shared zones (Authorities)

Take enforcement action against risky micromobility (Authorities)

Promote the use of appropriate helmets (Authorities)

Introduce rider education in secondary schools (Authorities)

Enable real-time safety interventions via telematics (Operators)

Provide post-trip feedback via telematics data (Operators)

Provide economic incentives for safe riding (Operators)

Implement mandatory initial rider training (Operators)

Verify age to start riding (Operators)

Safe Vehicles

Set universal technical requirements for e-scooter design (Authorities)

Adopt riding support systems in micromobility vehicles (Authorities)

Ensure systematic maintenance of micromobility (Operators)

Enable context-dependent maximum speed control using geofencing (Operators)

Restrict e-scooter access if tandem riding and/or alcohol use is detected (Operators)

Implement riding support systems in shared e-scooters (Operators)

Safe Management

Establish and collect data on distinct micromobility categories in safety statistics (Authorities)

Enable in-vehicle or in-app crash detection technology (Operators)



Safer Micromobility

George Yannis

NTUA Professor

Together with:
Virginia Petraki



Department of Transportation Planning and Engineering
National Technical University of Athens



Philippe Crist

Improving the safety of e-scooter users

Road Safety Performance Index debate - PIN Talk

13 May 2025

