



Methodology for the Evaluation of Safety Interventions

Eva Michelaraki

Transportation Engineer, PhD Candidate

Together with:

Christos Katrakazas, Ashleigh Filtness, Rachel Talbot, Graham Hancox, Chiara Gruden, Ariane Cuenen, Kris Brijs, Tom Brijs and George Yannis









The i-DREAMS project

- > 13 Project partners:
 - National Technical University of Athens

<u>Universiteit Hasselt</u>, <u>Loughborough University</u>, <u>Technische</u> <u>Universität München</u>, <u>Kuratorium für Verkehrssicherheit</u>, <u>Delft University of Technology</u>, <u>University of Maribor</u>, <u>OSeven</u> <u>Telematics</u>, <u>DriveSimSolutions</u>, <u>CardioID Technologies</u>, <u>European Transport Safety Council</u>, <u>POLIS Network</u>, <u>Barraqueiro Transportes S.A.</u>

- > Duration of the project:
 - 48 months (May 2019 April 2023)
- **Framework Program**:
 - <u>Horizon 2020</u> The EU Union Framework Programme for Research and Innovation - Mobility for Growth



Introduction

- Road crashes, fatalities and serious or slight injuries comprise important problems in public health
- In recent decades, automotive telematics and driver monitoring systems have been introduced in the industry in order to provide real-time and post-trip feedback to the driver
- A few driver monitoring technologies and platforms that have been used to record driving performance, focus on key risk indicators and provide safety
- Safety interventions have been indicated to significantly enhance driving behavior and road safety





Background

- The i-DREAMS project aims to define, develop, test and validate the concept of the 'Safety Tolerance Zone' (STZ), with a smart Driver, Vehicle & Environment Assessment and Monitoring System
- Driving task complexity indicators (e.g. road layout, weather conditions, time of the day) and driver background factors (e.g. fatigue, distraction, sleepiness) are taken into account
- A continuous real-time assessment is implemented to monitor and determine if a driver is within acceptable boundaries of safe operation (i.e. STZ)
- Safety-oriented interventions and post-trip feedback are provided in order to prevent drivers from getting too close to the boundaries of unsafe operation





Safety Tolerance Zone Concept

The **intervention mechanism** is based on the STZ concept, which is divided in three different phases:

- Normal Phase refers to the phase, where conditions at that point in time suggest that a crash is unlikely to occur and therefore, the crash risk is low and the operator is successfully adjusting their behavior to meet task demand; no real-time interventions are necessary
- Danger Phase is characterized by changes to the Normal Phase that suggest a crash may occur and thus, there is an increased crash risk. At this phase, a crash is not inevitable but becomes more likely; an alert will be offered
- Avoidable Accident Phase occurs when a collision scenario is developing, but there is still time for the operator to intervene to avoid the crash. At this phase, the need for action is more urgent to denote that if there are no changes or an evasive manoeuvre performed by the operator, a crash is very likely to occur; an intrusive warning signal will be provided





Objectives

- Provide a methodology for the evaluation of both real-time and post-trip safety interventions, which will be developed to improve driver safety through keeping the driver within the boundaries of the STZ
- Identify the appropriate assessment variables from the i-DREAMS platform, which are related to safety outcomes, safety performance goals, performance objectives and change objectives
- Define the crucial indicators, measurements and criteria for the quantification of the impact of realtime and post-trip safety interventions





Methodology

- Since the i-DREAMS interventions aim to improve driver safety, four different levels of driver safety are proposed:
 - Safety Outcomes
 - Safety Promoting Goals
 - Performance Objectives
 - Change Objectives
- The performance indicators and potential measurements that appeared to have the greatest effect on the assessment of interventions are presented

	Safety Outcomes	Safety Promoting Goals	Performance Objectives	Change Objectives	Potential measurements
			Fatigue		Distraction (Handheld mobile phone use, Hands on wheel)
	Frontal crash -Vehicle to Vehicle		Distraction Sleep deprivation		Inattention (Handheld mobile phone use, Hands on wheel)
S	- Vehicle to obstacle - Vehicle to VRU	Driver fitness	Acceleration		Fatigue/ Sleepiness (KSS score, Long driving hours, Time driving)
	Side crash -Vehicle to Vehicle - Vehicle to obstacle	Vehicle control	Deceleration Steering	Capability	Poor visibility/ Weather (wipers on)
	- Vehicle to VRU	Sharing the road with	Tailgating Lane discipline	Opportunity	Acceleration/ Deceleration (number of harsh
	Rear crash -Vehicle to Vehicle - Vehicle to obstacle	others	Overtaking	Motivation	accelerations/brakings and aggressiveness level)
	- Vehicle to VRU	Speed management	Forward collision avoidance	Behavior	Speeding (speeding percentage and average speed over speed limit)
al	Roll-over/derailment crash	Use of safety devices	Lane departure avoidance		Risky hours (driving during 00:00- 05:00)
9	Crash with injury for passengers		Vulnerable Road User collision avoidance		Overtaking
			Speeding (speed		Lane discipline
			limit exceedance)		Forward collision avoidance





Criteria

- The evaluation and the adoption of safety interventions can only be successful if the technology is effective in reducing the target risk and when it is also used efficiently by the driver
- In particular, the success of the i-DREAMS platform depends on whether drivers find the technology beneficial for their driving and safety
- In order to make the evaluations reach their full potential, their quality should be as high as possible
- > Two quality requirements are important in this respect:
 - user acceptance
 - reliability





User Acceptance

- Since user acceptance is related to the intention to use a system, it is based on individual attitudes, expectations and experience, obtained during actual use, as well as their subjective evaluation of expected benefits
- The change (or absence of change) in driver behavior in response to the interventions is an indication of acceptance
- If drivers do not accept the interventions, the technology will not increase their safety
- By observing driver's behavior, conclusions about acceptance can be derived. For instance:
 - if a driver presses or does not press the brake when receiving a warning about braking
 - if the brake response time when receiving a warning is too large





Reliability

- Reliability is typically used so that drivers can compare their individual skills and assess their strengths and weaknesses
- In its most basic form (i.e. how many times did the technology objectively pause to work or encounter problems), reliability can be also taken into account in the i-DREAMS platform
- A reliability assessment looking into whether the technology served its purpose, added value and allowed the user to depend on it in all situations is useful to gather
- For instance, real-time warnings may produce many false positives; thus, this will effect driving behavior





Before-after Analysis

- Before-after analysis can be used for the evaluation of interventions
- "Before" refers to a measurement being made before an intervention is introduced to a group, while "after" refers to a measurement being made after its introduction
- It is the most useful method in demonstrating the immediate impacts of short-term programs which offers a great evidence about intervention effectiveness
- It is suitable for both quantitative (i.e. safety outcomes and safety promoting goals) and observed qualitative indicators (i.e. performance objectives, change objectives)

X





Discussion

- Taking into account the on-road and simulator studies, the design of a customized feedback strategy will assist in performing the appropriate evaluation of interventions needed for the improvement of driver behavior
- A comparison between countries and different transport modes can be made, which will subsequently enhance the intervention performance evaluation and the quality of the assessment results









Methodology for the Evaluation of Safety Interventions

Eva Michelaraki

Transportation Engineer, PhD Candidate

Together with:

Christos Katrakazas, Ashleigh Filtness, Rachel Talbot, Graham Hancox, Chiara Gruden, Ariane Cuenen, Kris Brijs, Tom Brijs and George Yannis







